## HINIKER Conventional

Super-bright quad halogen headlights have up to twice the power of typical sealed beam lamps.

Externally mounted pump simplifies installation, comes off the truck with the plow.

Slick ¼" HMW poly moldboard surface resists dents, never needs paint.

30-inch tall high curve, high-density polyethylene moldboard is dent-resistant and corrosion-free. Snow flows easily for more efficient plowing. Optional rubber or polyethylene snow deflectors.

The high-tensile steel superstructure of the moldboard provides exceptional resistance to bending and bowing, for extra heavy-duty applications. 10 laser-cut steel ribs add exceptional strength.

Long-lasting cast ductile-iron skid shoes.

Pinch-free pivot point is 9 inches above the surface providing protection from higher obstacles such as curbs and parking barriers.

## The ULTMATE Performance With Hiniker Trip-Edge Straight Plows

The horizontal-truss moldboard design provides incredible strength, durability and resistance to bowing. Ten laser-cut support ribs add exceptional vertical strength. The corrosion-proof HDPE poly moldboard is dent-resistant with less surface friction for easier plowing and greater efficiency. Protection is provided by Hiniker's exclusive split trip-edge design.

- High clearance split trip-edge
- Extra strength trussed moldboard frame
- Super-bright quad halogen headlights
- Exclusive Hiniker Quick-Hitch mounting system





High clearance split trip-edges operate independently of one another, reducing stress and twisting forces on the plow.



**Convenient, compact fingertip control** mounts anywhere or can be hand held.

## 10 Foot Plow

Get professional plowing performance for your Ford F450/ F550, GM 4500/5500 or Dodge 4500/5500.

- 32" Tall high-capacity moldboard
- Corrosion-free, dent-resistant black HDPE
  polyethylene surface
- 14 Rib welded moldboard frame
- Two-section split trip edge with 6 trip springs for maximum protection
- 8 inch cutting edge—1/2 inch thick



## **CONVENTIONAL PLOWSpecifications:**

MODEL	7802	7902	10331
BLADE WIDTH	8'	9'	10'
BLADE HEIGHT	30"	30"	32"
VERTICAL RIBS	10	10	14
COMPRESSION TRIP SPRINGS	4	4	6
PLOW WIDTH @ 30° ANGLE	83"	93"	103"
CUTTING EDGE (HIGH CARBON 1084 STEEL)	³‰" x 6"	³∕8 <b>" x 6</b> "	½ <b>" x 8"</b>
TRIP PIVOT POINT HEIGHT	9"	9"	9.75"
WEIGHT (NET OF TRUCK MOUNTED HARDWARE)	733 lbs.	767 lbs.	938 lbs.

